

# Declaration of Performance

## SR15 Silicone Thin Coat Render




Declaration of Performance Number: CPR – 275/04

- 01 Unique identification code of the product-type: Ecorend SR15 Silicone Thin Coat Render
- 02 Type, batch or serial number or other identifying mark to identify the construction product as set out in Article 11 (4): **Batch Number:**  
**See product packaging**
- 03 Intended use as foreseen by the manufacturer of the construction product in accordance with the harmonised technical specification:  
**Internal and external rendering on walls**
- 04 Name, registered trade name or registered trade mark and contact address of the manufacturer as set in article 11 (5): **La Roc, Dalton Industrial Estate, Dalton, Thirsk, North Yorkshire YO7 3HE**
- 05 Name and contact address of the authorised representative who has received a mandate for the tasks set out on Article 12 (2): **Not Relevant**
- 06 System or systems for assessment and verification of constancy of performance of the construction product in accordance with annex V:  
**System 2+**
- 07 In the case of declaration of performance concerning a construction product covered by a harmonised standard: **EN 15824:2009 - Water diluted external render based on organic binder**
- 08 In the case of declaration of performance concerning a construction product for which a European Technical assessment has been issued: **Not Relevant**
- 09 Declared performance

Reaction to fire	Class C (Class 0 as a part of external insulation system)
Water vapour permeability	V2 (Medium)
Water absorption	W3 (low)
Adhesion	> 0.3MPa
Durability	Not applied
Thermal conductivity	(λ10, dry) 0.66 W/mK (EN 1745 Table A.12 mean value; P = 90%)

- 10 The performance of the product identified in points 1 and 2 is in conformity with the declared performance of point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

### CE MARKING ACCORDING TO CPR 305/2011 AND EN 15824:2009

	
La Roc Dalton Industrial Estate, Dalton, North Yorkshire YO7 3HE <b>14</b>	
<b>Ecorend SR15 Silicone Thin Coat Render</b>  Water diluted external render based on organic binder  EN 15824:2009	
Reaction to fire	Class C (Class 0 as a part of external insulation system)
Water vapour permeability	V2 (Medium)
Water absorption	W3 (low)
Adhesion	> 0.3MPa
Durability	Not applied
Thermal conductivity	(λ10, dry) 0.66 W/mK (tab. mean value; P = 90%)

**Signed for and on behalf of the manufacturer by:**  
Gavin Bagshaw – Technical Information & Customer Support Lead



**Place and date of issue:**  
12th September 2018 - Dalton/Thirsk